



SITEWARDEN SD400RF

Radio Linked Smoke Detector



QUICK START GUIDE

The Sitewarden SD400RF smoke detector is designed to be used within the Sitewarden RF fire alarm system. It provides the user with the flexibility to install radio linked smoke detectors in the ideal locations required for your system.

All Sitewarden SD400RF are required to be paired to a SP400RF to be used as part of the Sitewarden RF system. Using the instructions provided with the SP400RF Fire Alarm, please set up the MASTER unit first and then proceed with the pairing of the SD400RF smoke detector, by following the steps overleaf.

FIRECHIEF® SITEWARDEN SD400RF

Radio Linked Smoke Detector

PAIRING A SD400RF SMOKE DETECTOR

1. Locate the battery tab on the rear of the detector and also the TEST button on the side of the detector. Prepare to press the TEST button within 20 seconds of removing the battery tab.



2. Remove the battery tab in the base of the detector. You will hear a confirmation beep



3. Within 20 seconds, press the TEST button on the edge of the smoke detector. The test button will flash blue.



4. Then press and release the PROG button on the MASTER unit. A 'd' will appear in the LED display and the smoke detector will start to emit a series of beeps.



5. Press and release the TEST button on the smoke detector. You will hear a confirmation tone and the units are now paired.



6. Now install the base of the detector in the location required using suitable fixings.



7. When the base is fixed, the detector can then be installed by locating it in the base and turning clockwise until you hear a click and the detector is firmly held in the base.

